

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/059855 A1

(51) International Patent Classification⁷: **G08B 13/24**

(21) International Application Number:
PCT/DK2004/000876

(22) International Filing Date:
16 December 2004 (16.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2003 01862 16 December 2003 (16.12.2003) DK

(71) Applicant and

(72) Inventor: **JORGENSEN, Poul, Richter** [DK/DK];
Saugskærvej 16, Thurø, DK-5700 Svendborg (DK).

(74) Agent: **TROESCH SCHEIDEGGER WERNER AG**;
Shwäntenmos 14, 8126 Zumikon (CH).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,


AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **IMPROVED RESONANCE SECURITY TAG AND METHOD OF PRODUCING SUCH A TAG**



(57) Abstract: A resonance security tag (1) comprises a dielectric foil material (2) provided with conductive material layer patterns (3-7) on both sides. The conductive material layer patterns are formed to provide an inductor (3) and a capacitor (4, 6) positioned inside the inductor (3), and mutually connected to form a resonance circuit. By cutting (9) the capacitor (4, 6) free of the dielectric foil material (2) and folding the capacitor (4, 6) away from the position inside the inductor (3), this part is left free for the penetration of magnetic flux through the inductor (3), whereby the detection level is improved and a possibility of reducing the size of the resonance security tag is provided.

WO 2005/059855 A1